Engineering data sheet

Chapter: SV Acc

Sheet No.: 305751

SV Adapter 1" - M40x1.5

Item numbers covered by this datasheet

SV Adapt 1"ISO - Mx1.5 305750 SV Adapt 1"npt - Mx1.5 305751

General

An adapter which allows to connect the SV Tee and Pipe kit to a pipe system using npt thread.

Notice that the pipe system should be rated for the high pressure part of the system unless special precautions are made.

13 I W

Page: 1 of 2

Specifications

Pressure

0-400 Work: > 1600 bar Proof (burst): -20 to +70°C **Temperature**

400mm2 (ø22mm) Flow way

Thread

T1: 1" npt (ansi)

T2: M40x1.5 (Interfaced to Fi

Stainless steel, EPDM **Materials**

Dimension

52mm H: 41mm Hex W: Weight: 0.25 kg

Markings

Label indicating ISO or npt thread

l	Pos.	Item*	Description	Material						
	13	305240	SV Adapter 1"npt-M40×1.5 SV Adapter 1"ISO-M40×1.5	SS304 SS304						
l	16	2260152	O-ring 26.0×1.5	PUR						
	*Recommended replacement item numbers.									
i	Fire Eater SV or Ci parts)									

Document: 305751 SV A	dapter 1 - M40x1.5	1	Text		
Category:	ld: OLRA	3			
SV-CiV system	Rev:2013-11-11	4			
4.4	4.				
	/ølundsvej 17 DK- 3400 Hillerød Fel +45 7022 2769	7			
		8			
	% Fax +45 7023 2769				

Engineering data sheet

Chapter: SV Acc

Sheet No.: 305751

Page: 2 of 2


Installation

Make sure O-rings are clean and well lubricated.

Use PTFE tape or other thread sealant on the tapered npt thread to ensure tight installation. Tighten the npt part of the adapter before connecting the M40 thread.

When the npt thread is tightened the M40 thread is connected. If used with SV parts ensure that O-ring is seated well inside the adapter and insert interface carefully making sure not to damage the O-ring. If Ci parts are used, remove the O-ring inside the adapter and use the O-ring placed in the Ci part, carefully align the parts making sure not to damage the O-ring.

Tighten the union by hand to make a tight installation additional tightening may be required to ensure parts from becoming loose due to vibrations etc.



Maintenance

Clean regularly with mild detergent.

Do not use chlorine or other solvents unsuitable for brass and stainless steel.

Document: 305751 SV Adapter 1 - M40x1.5			Text
Category:	ld: OLRA	3	
SV-CiV system	Rev:2013-11-11	4	
4.		5	
Vølundsvej 17 DK- 3400 Hillerød		6	
		7	
	DK- 3400 Hillerød Tel +45 7022 2769	8	
FIRE EATER 4/	FIRE EATER % Fax +45 7023 2769		