Engineering data sheet

Chapter: Signalisation Page: 1 of 1

Sheet No: 407022

Flash Red 24VDC

The Xenon Beacons have been designed to complement other products in the range both technically and aesthetically.

The beacons will mount neatly onto a Squashni base sounder to provide a low profile sounder/beacon. Similarly the beacon can be supplied coupled to a Roshni electronic sounder to provide a high output audio visual unit.

The beacons have a built-in terminal block for ease of installation and utilise the same range of bayonet fitting bases as other products in the range.

(The mains beacon is supplied with a lockable, deep or 'U' base only.)



General specifications

Voltage: 20-30 VDC

Current: 90mA @ 24VDC

Power rating: 2.1W
Flash rate: 60 min-1
Flash Energy: 1.35j
Integrity: IP65

Cableway: Knock-out for M21 cable glands.

Colour: Red

Dimension: D x H: ø93 x 100 mm



Document: 407022 Flash red 24VDC		1	Text
		2	
Product:	ld: KP	3	
Electrical comp.	Rev: 21.05.10	4	
Vølundsvej 17 DK- 3400 Hillerød Tel +45 7022 2769		5	
		6	
		7	
		8	
FIRE EATER % Fax	Fax +45 7023 2769	9	
7 7712 2711 211 /3			<u>'</u>