Sheet No.: 305490

Tool: Ci IV8 Separator Disc tool


General

The Ci IV8 Separator Disc tool is used to remove/fit the separator disc [16] and piston [23] on the Ci IV8 valve.

Performing maintenance on the Ci IV8


To remove the separator disc [16], item no. 305011, follow the following steps:

- 1. Make sure the Ci IV8 valve is depressurized.
- 2. To access the separator disc, remove the actuator plug [20] following the procedure described on datasheet 305491 and extract drive piston [18], item no. 305018 (with rod and other parts), and place it in the act plug. Remember to loosen the set screw [2] first.



- 4. Using a 4mm hex wrench through the 5mm hole, carefully push the piston [23] out of the valve. Be particularly careful not to scratch the inside bore of the valve body.
- 5. When maintenance is completed, place the new piston [23] on the separator disc tool. O-rings must be lubricated (use lubricant, item no. 203012). Damaged or dirty o-rings must be replaced.
- 6. Carefully insert the piston and separator disc into the valve and tighten the separator disc to 10 Nm. Remove the separator disc tool. When tightened, the separator disc must be flush with the shoulder inside the valve's body.
- 7. Carefully insert the drive piston [18] and actuator plug [20] into the valve and tighten the actuator plug as described in datasheet 305491. Remember to tighten the set screw [2] after assembly.
- 8. Check that the piston is seated properly by pushing it back with a 4mm hex wrench though the 5 mm hole.

NEVER perform maintenance on pressurized components as this will discharge the system and may cause injuries.



Document: 305490 Tool IV8 Separator Disc.doc	Text			
Product: Id: KP	3			
Tool Rev: 12.11.12	4			
44	5			
	6			
Vølundsvej 17 DK- 3400 Hillerød	7			
DK- 3400 Hillerød Tel +45 7022 2769	8			
FIRE EATER % Fax +45 7023 2769				




Engineering data sheet


Chapter: Tool

page: 2 of 2

Sheet No.: 305490



Dimensions



Document: 305490 Tool IV8 Separator			Text
Disc.doc		1	
		2	
Product:	ld: KP	3	
Tool	Rev: 12.11.12	4	
Vølundsvej 17 DK- 3400 Hillerød		5	
		6	
		7	
	DK- 3400 Hillerød Tel +45 7022 2769	8	
FIRE EATER 1/5	FIRE EATER % Fax +45 7023 2769		