

Cylinder 2-200 w. Nitrogen

General

Complete steel cylinder with Nitrogen and hand wheel valve used in Fire Eater INERGEN fire extinguishing systems as a pilot cylinder.

Specifications

Dimension

Diameter: 102 mm
 Wall thickness: > 2.5 mm
 Height cyl.: 345 mm
 Height cyl. incl. HWV: 445 mm
 Weight (filled): 3.5 kg

Pressure

Fill @ 15°C: 200 bar
 Test: 300 bar

Volume

Water: 2 litres
 Nitrogen: 0.4 m³

Colour

EN 1089/3
 Cylinder: Green (RAL6018)

Standard & approval

ISO 9809-1, π
 TPED EC1999/36

Material

34CrMo4

Tread

Cylinder: 17E
 Valve outlet: W24.32



Installation

Cylinders must be fixed firmly to wall or floor with suitable brackets.

Maintenance

Recertification (testing) every 10 years, or as per local authorities having jurisdiction.

Pos.	Name	Quantity	Item
1:	Cylinder 2-200	1	400009
2:	Hand wheel valve W24.32	1	603210
3:	Nitrogen (m ³)	0.4	200000

Document: 400011 Cylinder 2-200 W24		Pos 1	Text
Product: Mech. components	Id:NATH	2	
	Rev: 04-08-2022	3	
		4	
		5	
		6	
		7	
		8	



Vølundsvej 17
 DK- 3400 Hillerød
 Tel +45 7022 2769
 Fax +45 7023 2769