

## Alarm point Flash amber with sound Excel Lite

### General

A combined changeable-tone sounder with built-in flash.

### Specifications

Voltage:	10-30 VDC
Current:	
Sounder	39 mA max.* @ 24VDC
Flash	16 mA @ 24VDC
Termination:	Screw terminals, 0.28-2.5mm <sup>2</sup> wire
Sound rate:	The sound can be changed in frequency and timing by a DIL-switch
Flash rate:	1/sec.
Integrity:	IP66
Cableway:	Knock-out for M20 cable glands
Colour body/lens:	Red/Amber
Number of tones:	Depending on the DIL-switch setting
Materials:	Polycarbonate, ABS
Dimension	
D×H:	ø92×109 mm
Weight:	0.240 kg

(\* ) The current depends on the sound rate.



Compliance:	EN54-3
CPR No:	2831-CPR-F1834

<b>Document:</b> 406043 Alarm point Flash Amber with sound Excel Lite.docx		1	Text
		2	
<b>Product:</b> Elec accessories	Id: MRP	3	
	Rev: 2024-04-05	4	
		5	
		6	
		7	
		8	
		9	



Vølundsvej 17  
DK- 3400 Hillerød  
Tel +45 7022 2769  
Fax +45 7023 2769