

Cable ATEX 4x0.75mm2

Item numbers covered by this data sheet

Fire-Eater item number and name	OEM item number
18045166-39 Cable ATEX 4x0.75mm2	LAPP Ölflex EB CY

OEM data sheet

U.I. Lapp GmbH	DATA SHEET	 LAPP KABEL
----------------	-------------------	---

ÖLFLEX® EB CY

DB 0012640

valid from: 2015-02-11

Application

ÖLFLEX® EB CY are PVC control cables with blue outer sheath for occasional flexible use and fixed installation in intrinsically safe circuits. They are among others designed for use in dry, damp and wet rooms. Outdoor use: They may only be installed with UV protection and considering the temperature range. At room temperature they are widely resistant to certain oils and resistant to acids. They are suitable for non-continuously recurring movement without tensile load. Continuous operation movement, compulsory guidance respectively usage on cable drums or pulleys or under a tensile strain of more than 15 N / mm² conductor cross section are not allowed.

Application range:

Installation of intrinsically safe circuits, where a special cable marking for hazard area type "i" - intrinsic safety is specified; The cables meet the requirements of DIN EN 60079-14(VDE 0165-1):2012-2 potentially explosive atmosphere. The screen is a protection against electrical interference.

Design

Design	based on DIN EN 50525-2-51 resp. VDE 0285-525-2-51
Conductor	fine wire strands of bare copper acc. to IEC 60228 resp. VDE 0295, Class 5
Core insulation	LAPP special PVC compound P8/1 PVC compound TI2 acc. to DIN EN 50363-3 resp. VDE 0207-363-3 with increased Requirements acc. to Lapp specification
Core identification	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with white numbers acc. to DIN EN 50334 resp. VDE 0293-334
Wrapping	plastic foil
Screen	braid of tinned copper, coverage = 85% (nominal value)
Outer sheath	PVC compound TM2 acc. to DIN EN 50363-4-1 resp. VDE 0207-363-4-1 with increased requirements acc. to Lapp specification colour: blue, similar RAL 5015.

Electrical properties

Nominal voltage	300 / 500 V
Operating Voltage	< 50 V AC resp. < 75 V DC in intrinsically safe circuits
Test voltage	Core/Core: 3000 V AC Core/Screen: 2000 V AC

Mechanical and thermal properties

Min. bending radius	occasional flexing: 20 x outer diameter fixed installation: 6 x outer diameter
Temperature range	occasional flexing: -5 °C up to +70 °C max. conductor temp. fixed installation: -40 °C up to +80 °C max. conductor temp.
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2
Tests	acc. to IEC 60811 resp. VDE 0473-811, VDE 0472, EN 50395, EN 50396
EC-Directives	This cable is conform to the EC-Directives 2006/95/EC (Low Voltage Directive) and 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).

Originator: KASC / PDC approved: HAPF / PDC	Document: DB0012640EN	Page 1 of 1
--	-----------------------	-------------

All deviations from this specification are subject to explicit consent of U.I. Lapp GmbH. All rights reserved acc. to DIN 34.
PD 0019/2_1_11.09EN