


Class 6000 hex head plug

Item numbers covered by this datasheet

76290806 ASTM 6000 Hex Head Plug 1" npt 76290808 ASTM 6000 Hex Head Plug 1½" npt 76290809 ASTM 6000 Hex Head Plug 2" npt

General

High-strength galvanized cast iron fittings conforming to ASME B16.11, for use in high-pressure fire extinguishing systems. The class 6000 marking ensures mechanical properties of the fittings have been verified.



Specifications

| Nominal Size | DN | Α | F | Н | Mass |
|--------------|----|----|-------|----|------|
| | mm | mm | mm | mm | kg |
| 1 | 25 | 21 | 50,80 | 10 | 0,25 |
| 1½" | 40 | 22 | 63,50 | 16 | 0,6 |
| 2" | 25 | 22 | 63,50 | 18 | 1 |

Marking

In line with ASME B16.11, the fittings are marked with the material grade, Class, size, and manufacturer.

Installation

See data sheet: 51 Pipes - Pipes regarding details for pipe system and installation.

Standards

Pipe fittings are rated for working pressure up to 400bar in extinguishing system. Certificates with material composition and mechanical properties are available.

Dimensions: ASME B16.11 Thread: ASME B1.20.1 Material: ASTM A105

| Document: | ci ASTM plug | Revision: 2025-01-06 | Vølundsvej 17 DK-3400 Hillerød | +45 7022 2769 www.fire-eater.com |
|-----------|---------------|-------------------------|-----------------------------------|-------------------------------------|
| Part no.: | 7629080x | ID: DAJO | | |
| Category: | Control inert | Chapter 51 Pipe systems | | Page 1 of 1 |